

Multifunctional 80mm Thermal Receipt Printer GA-F350



Easy front-feeding and spill-proof design



Front long LED indicator for prompt printing status indication

Features

- Easy paper load, easy front-feeding and spill-proof design
- High print speed up to 300mm/sec
- Cover closing buffer design
- Allow desktop and wall-mount installation
- Various printer ports including USB, Rs232, Ethernet, Bluetooth and Wi-Fi
- Front long LED indicator for prompt printing status indication
- Built-in loudspeaker for receipts printing reminder, ideal for kitchen noisy environment



Specification

Printing	
Print method	Direct thermal
Resolution	203dpi
Print width	64/72mm
Dot density	512/576dot/line
Print speed	300mm/s
Interface	Serial+USB+Ethernet, USB+WIFI, USB+Bluetooth
Paper	Paper width: 79.5 ±0.5 Paper diameter:120mm
Line space	3.75mm(can be adjustable)

General	
Data	128K bytes
NV Flash	256K bytes
Cash drawer out	DC 12V/1A
Power supply	AC 110V/220V 50~60Hz DC 24V/2A
Weight	1.35kg
Dimension	136*197*141mm
Work environment	Temperature: 0~45°C, Humidity: 10~80%
Storage environment	Temperature: -10~60°C, Humidity: 10~90%
Reliability	150km

Barcode	
Character Size	ANK Font Font A: 12x24dots Font B:9x17dots Simplified/Traditional Chinese Character: 24x24dots
Code page	PC437/Katakana/PC850/PC860/PC863/ PC865/West Europe/Greek/Hebrew/ East Europe/Iran/WPC1252/PC866/ PC852/PC858/IranII/Latvian/Arabic/ PT151,1251/PC737/WPC/1257/Thai Vietnam/PC864/PC1001/(Latvian)/ (PC1001)/(PT151,1251)/(WPC1257)/ (PC864)/(Vietnam)/(Thai)
Barcode mode	UPC-A/UPC-E/JAN13(EAN13)/JAN8 (EAN8)CODE39/ITF/CODABAR/ CODE93/CODE128/QRCODE
Fonts	Gb18030

