



SURPASS SERIES – Thermal Transfer Label and Wristband Printer
2" Wide GS-2206T
VERSATILE, HIGH PERFORMANCE, COST EFFECTIVE



KEY FEATURES

- 152.4 mm (6") per second print speed for 203 DPI.
- 300 meter (984') ribbon supply on a 25.4 mm (1") core (coated outside).
- 400 MHz 32-bit ARM9 processor with 64 MB SDRAM, 32 MB Flash memory or 64 MB SDRAM, 128 MB Flash memory.
- Internally scalable true type font engine.
- USB Host for scanner or PC keyboard.
- Firmware emulates EPL, ZPL, ZPL II, DPL, TSPL.
- BarTender Free Windows® drivers and label design software (available via download).
- Provide Windows printer utility, Windows SDK and Android SDK.
- Solution for printing medial, government, entertainment and pets wristbands.

SURPASS SERIES -

2" Desktop Thermal Transfer Label Printer

PRINTER MODEL	GS-2206T	GS-3205T
Level	Economic	Economic
Resolution	8dots/mm (203DPI)	12dots/mm (300DPI)
Printing Method	Thermal Transfer & Direct Thermal	
Max. print speed	152.4mm (6")/second	127mm (5")/second
Max. print width	54mm (2.13")	54mm (2.13")
Max. print length	2,794mm (110")	1,016mm (40")
CPU	400MHZ, 32-bits, ARM9	
Memory RAM	64MB SDRAM	
Memory ROM	32MB Flash Memory(128MB Flash Memory Option)	
Interface	USB 2.0 High Speed 480Mbps USB Host 2.0, for scanner or PC keyboard Internal Bluetooth 4.0 (factory option) Internal Wi-Fi (factory option)	
Real Time Clock	N/A	
Buzzer	N/A	
Dealer options	N/A	
Sensors	Head open sensor, Ribbon end sensor, Reflective sensor (moveable), Front-Reflective sensor	
Power	External universal switching power supply Input: AC 100-240V, 2.5A, 50-60Hz, Output: DC 24V, 2.5A, 60W	
User Interface	1 power switch, 2 buttons (Feed & Pause), 3 LEDs (Online, Error, Ribbon status)	
Internal fonts	8 alpha-numeric bitmap fonts True type font engine (need download scalable font file)	
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Pleassy, PostCode, Telepen	
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix	
Rotation	Font and barcode support 0, 90, 180, 270 degree	
Printer language	Compatible to EPL, ZPL, ZPL II, DPL, TSPL	
Ribbon	300m long, max. OD 67mm, 1" core(ink coated outside)	
Ribbon Width	30mm~60mm(1.18"~2.36")	
Media type	Continuous, die-cut, black mark, fan-fold, notched (outside wound)	
Media width	20~60mm (1.18"~2.36")	
Media thickness	0.06~0.254mm (2.17~10mil)	
Media core diameter	25.4mm (1")	
Label roll capacity	127mm (5")OD	
Label length	5~2,794mm (0.2"~110")	5~1,016mm (0.2"~40")
Physical dimension	160mmx170mmx280mm (WHD)	
Weight	1.72kg	



Enclosure

ABS plastic

Certification

FCC, CE, CCC, BIS, CB

Environment condition

Operation: 5~40°C, 25~85% non-condensing
Storage: -40~60°C, 10~90% non-condensing

Environment concern

Comply with RoHS, REACH, WEEE

Accessories

Windows labeling software CD disk/Quick start guide/USB cable/Power cord/External universal switching power supply/1" ribbon spindle x 2 for 300m ribbon

Limited warranty

Printer: 2 years
Print head: 25km (1 million inches)/12 months
Roller: 50km (2 million inches)/12 months

User options

External roll mount

Gainscha Auto ID Co., Ltd.

Add: Zone G, 2nd floor, Workshop No. 1, No. 15 pingbei
2nd Road, Xiangzhou District, Zhuhai

Tel : +86 756 3965698
Fax : +86 756 3965694
E-mail : sales@gainscha.com
Website: gainscha.com.tw | gainscha-aidc.com